

MODEL	AIRMAX	
DESCRIPTION	UOM	PARAMETRIC VALUE
TYPE		WALL MOUNTED / PEDESTAL
AIR FILTER		5 MICRON FILTER WITH MANUAL DRAIN
INLET AIR PRESSURE	BAR	8 to 10 consistently
INPUT POWER SUPPLY		230 V AC , 50HZ
POWER	WATTS	8
CONTROL SYSTEM		MICRO PROCESSOR BASED
KEYPAD TONE		BEEP
END OF INFLATION		LONG BEEP
MAX INFLATING PRESSURE	PSI	Max 130 psi
TYRE INFLATION		Air with single hose point with air chuck connectors
INFLATING HOSE		POLYURETHANE HOSE
INFLATING HOSE LENGTH	MTR	10
KEYPAD		5 KEYS DOME MEMBRANE TYPE
PRESSURE TRANSMITTER		NON SMART TYPE
PRESSURE TRANSMITTER MEASURING RANGE	BAR	0 - 15
END CONNECTION	INCH	1/4
DISPLAY		2NOS 7 SEGMENT LED FOR BOTH SET PRESSURE & TYRE PRESSURE
INDICATION		INF,DEF , PSI/BAR, CHECK LEAK
INGRESS PROTECTION		IP65
CABINET MOC		POWDER COATED CRC SHEET
TYPE OF PACKING		carton box