

MODEL	NITROPAQ 10 S	
DESCRIPTION	UOM	PARAMETRIC VALUE
TYPE		PSA , TWIN TOWER
N2 RECEIVER CAPACITY	LTR	40
AIR FILTER		5 MICRON FILTER WITH MANUAL DRAIN
N2 PURITY	% OF N2	95.5 - 99
INLET AIR PRESSURE	BAR	8 to 10 consistently
INPUT POWER SUPPLY		230 V AC , 50HZ
CONTROL SYSTEM		MICRO PROCESSOR BASED
KEYPAD TONE		BEEP
END OF INFLATION		LONG BEEP
POWER	WATTS	8
N2 PRESSURE	PSI	Max 130 psi
TYRE INFLATION		N2 with single hose point with air chuck connectors
INFLATING HOSE		POLYURETHANE STRAIGHT HOSE
INFLATING HOSE LENGTH	MTR	8
PRESSURE GAUGE		2nos, Panel mounted, Bourdon tube to indicate N2 & Air pressure
KEYPAD		5 KEYS DOME MEMBRANE TYPE
PRESSURE SWITCH		Pressure based SPDT switch
PRESSURE TRANSMITTER		NON SMART TYPE
PRESSURE TRANSMITTER MEASURING RANGE	BAR	0 - 15
END CONNECTION	INCH	1/4
HOUR METER		N2 GENERATION HOURS
TYRE COUNT		For N2 & AIR inflation
DISPLAY		2NOS 7 SEGMENT LED FOR BOTH SET PRESSURE & TYRE PRESSURE
INDICATION		VACCUM , PSI/BAR, CHECK LEAK
CABINET MOC		POWDER COATED CRC SHEET
VEHICLE SUITABLE FOR		MOTOR CYCLE, CARS
TYPE OF PACKING		7 ply carton box with wooden reaper at bottom