

<b>MODEL</b>	<b>NITROPAQ 20</b>	
<b>DESCRIPTION</b>	<b>UOM</b>	<b>PARAMETRIC VALUE</b>
TYPE		PSA , TWIN TOWER
N2 RECEIVER CAPACITY	LTR	90
AIR FILTER		5 MICRON FILTER WITH AUTO DRAIN
N2 PURITY	% OF N2	95.5 - 99
INLET AIR PRESSURE	BAR	10 to 12 consistently
INPUT POWER SUPPLY		230 V AC , 50HZ
CONTROL SYSTEM		MICRO PROCESSOR BASED
KEYPAD TONE		BEEP
END OF INFLATION		LONG BEEP
POWER	WATTS	8
N2 PRESSURE	PSI	Max 150 psi
TYRE INFLATION		N2 with single hose point with air chuck connectors
INFLATING HOSE		POLYURETHANE BRAIDED
INFLATING HOSE LENGTH	MTR	10
PRESSURE GAUGE		2nos, Panel mounted, Bourdon tube to indicate N2 & Air pressure
KEYPAD		5 KEYS DOME MEMBRANE TYPE
PRESSURE SWITCH		Pressure based SPDT switch
PRESSURE TRANSMITTER		NON SMART TYPE
PRESSURE TRANSMITTER MEASURING RANGE	BAR	0 - 15
END CONNECTION	INCH	1/4
HOUR METER		N2 GENERATION HOURS
TYRE COUNT		For N2 & AIR inflation
DISPLAY		2NOS 7 SEGMENT LED FOR BOTH SET PRESSURE & TYRE PRESSURE
INDICATION		VACCUM , PSI/BAR, CHECK LEAK
CABINET MOC		POWDER COATED CRC SHEET
VEHICLE SUITABLE FOR		MOTOR CYCLE, SUV, LCV , etc.
TYPE OF PACKING		7 ply carton box with wooden reaper at bottom